

R6060 QLC Series

DapuStor® Enterprise NVMe SSD



Specifications

PCN (Product Code Name)	R6060			
Capacity (TB)	15.36	30.72	61.44	122.88
Form Factor	U.2 15mm			
Interface	PCIe 5.0 x 4/2x2, NVMe 2.0			
Read BW @128KB MB/s	14000	14000	14000	14000
Write BW @128KB MB/s	4000	4000	4000	4000
Rand. Read @4KB KIOPS	3000	3000	2800	2800
Rand. Write KIOPS	40 @16KB		25 @32KB	
Rand. Latency R/W μ s	80/25			
Seq. Latency R/W μ s	7/8			
Max. Power (W)	25			
Idle Power (W)	5			
Flash Type	3D Enterprise QLC NAND Flash			
Endurance	0.6 DWPD			
MTBF	2.5 million hours			
UBER	1 sector per 10^{18} bits read			
Warranty	5 years			

*Differences in hardware, software, or configuration will affect actual test results.

✉ mkt@dapustor.com

☎ +86 400-9938-968

🌐 <http://www.dapustor.com/>

📍 Chuangtou Building, Longgang District, Shenzhen, China



Copyright© DapuStor Corporation. All rights reserved.

No third party can extract or copy any part or the whole content of the document without the permission of the company. And no third party can distribute it in any way.

All trademarks in this document belong to DapuStor Corporation.

DapuStor