

Roealsen[®] 6 R6 Series.

DapuStor Enterprise NVMe SSD

PCIe 5.0



The DapuStor[®] Roealsen[®] R6 series features the latest PCIe 5.0 interface and 3D eTLC NAND Flash. Supporting the NVMe 2.0 protocol, it offers twice the performance of PCIe 4.0 SSDs. This series offers multiple enterprise-grade advanced features, providing industry-leading performance and cost-effective solutions for critical business operations, cloud infrastructure, and artificial intelligence.

| Superior Performance

DapuStor[®] R6 series PCIe Gen5 SSD offers a 100% improvement in bandwidth and IOPS performance compared with Roealsen5 Series. The DP800 controller optimizes the I/O path, significantly reducing latency and enhancing QoS in mixed read/write operations.

14.5/11GB/s

SR/SW (MB/s)

3500K/1000K

RR/RW (IOPS)

48/7μs

RR/RW latency (μs)

| Industry-Leading NAND Flash

DapuStor R6 series utilizes the latest 3D eTLC NAND Flash for high efficiency. Innovative machine learning technology minimizes NAND retries at the system level and timely predicts NAND workloads in complex scenarios to prevent systemic failures.

| Premier Gen5 Transparent Compression SSD

DapuStor is in the first wave to launch a PCIe Gen5 transparent compression SSD, leveraging the built-in application processor platform and compression module in the DP800. It supports user capacity expansion within the same physical capacity, enhancing overall data storage density based on compressibility, or improves endurance and steady-state random write performance with data compression and user capacity unchanged.

| Advanced Features

- NVMe 2.0 Features**
 Supports online upgrades, up to 128 namespaces, multiple streams, atomic writes, and advanced data management functions, including sanitizing, copying, verifying, and comparing.
- OCF 2.5 Compliance**
 Follows the OCF 2.5 specification, facilitating advanced features such as Telemetry, Latency Monitor, and Thermal Throttle.
- Supports SR-IOV**
 Supports up to 64 VFs
- Supports FDP**
 Enhances steady-state random write performance and significantly reduces write amplification, achieving WAF=1 in specific conditions
- Supports NVMe-MI 1.2**
 Features include MCTP Over I2C/SMBUS, Over PCIeVDM, out-of-band upgrades, NVMe-MI Send and NVMe MI Receive.
- End-to-End Data Protection**
 Includes DIF/DIX, five sector format types, protection information (Type 1, 2, 3) and detailed logging capabilities, ensuring comprehensive user data safety
- Enterprise Security Features**
 Supports Secure Boot, Firmware Security Verification, Format, Sanitize and other enterprise security features.

Roedalsen® 6 R6 Series

DapuStor Enterprise NVMe SSD



Specifications

PCN (Product Code Name)	R6101					R6301				
Capacity (TB)	1.92	3.84	7.68	15.36	30.72	1.6	3.2	6.4	12.8	25.6
Form Factor	U.2 15mm									
Interface	PCIe 5.0 2x2, NVMe 2.0									
Read BW 128K (MB/s)	14000	14000	14500	14500	14000	14000	14000	14500	14500	14000
Write BW 128K (MB/s)	3200	6500	11000	11000	10000	3200	6500	11000	11000	10000
Rand. Read 4K KIOPS	2000	2500	3500	3400	3400	2000	2500	3500	3400	3400
Rand. Write 4K KIOPS	210	330	450	500	420	350	610	950	1000	900
Rand. 4K Latency (μs)	48/7									
Seq. 4K Latency (μs)	7/7									
Typical Power (W)	11	15	18.5	22	22	11	15	18.5	22	22
Idle Power (W)	5									
Flash Type	3D eTLC NAND Flash									
PN (Model Number)	DPRE5102T OTK01T9010	DPRE5104T OTL03T8010	DPRP5108T OTL07T6010	DPRP51016T TL15T3010	DPRP51032T TM30T7010	DPRE5102T OTK01T6010	DPRE5104T OTL03T2010	DPRP5108T OTL06T4010	DPRP51016T TL12T8010	DPRP51032T TM25T6010
Endurance	1					3				
MTBF	2.5 million hours									
UBER	1sector per 10 ¹⁸ bits read									
Warranty	5 years									


*Differences in hardware, software, or configuration will affect actual test results.

✉ mkt@dapustor.com

🌐 www.dapustor.com

☎ +86 400-9938-968

📍 Chuangtou Building, Longgang District, Shenzhen, China



Copyright© DapuStor Corporation. All rights reserved.

No third party can extract or copy any part or the whole content of the document without the permission of the company. And no third party can distribute it in any way.

All trademarks in this document belong to DapuStor Corporation

DapuStor